

## Turbo Granulators

### 99% Clean Material

The addition of a “turbo” device or refiner, can increase productivity of a granulator mill by 20-30%. By changing the geometry of the cable being processed Stokkermill Turbo Granulators allow operators to maximize material processing therefore creating greater profit.



**STOKKERMILL**  
RECYCLING MACHINERY

2000 TURBO	
Power	32 kW
Production	375/551 lb
Dimensions	121" x 66" x 136"
Weight	4079 lb



**STOKKERMILL**  
RECYCLING MACHINERY

3000 TURBO	
Power	40 kW
Production	551/772 lb
Dimensions	121" x 69" x 136"
Weight	4960 lb



**STOKKERMILL**  
RECYCLING MACHINERY

4000 TURBO	
Power	52 kW
Production	660/880 lb
Dimensions	132" x 69" x 137"
Weight	5290 lb

# MULTI-FLEX Turbo Granulators

## Maximize Wire Profit

Stokkermill MULTI-FLEX Turbo Granulators are designed for milling copper or aluminum cables and sorting the metal from the insulation. They are composed of two parts; the first is the mill blades and the other is the turbo-separating sections. The combination of these parts allows for a higher performance.



**STOKKERMILL™**  
RECYCLING MACHINERY

<b>M 60</b>	
Power	60 kW
Production	770/1100 lb
Dimensions	179" x 65" x 114"
Weight	9150 lb



**STOKKERMILL™**  
RECYCLING MACHINERY

<b>M 80</b>	
Power	70 kW
Production	880/1320 lb
Dimensions	121" x 69" x 114"
Weight	9920 lb



**STOKKERMILL™**  
RECYCLING MACHINERY

<b>M 100</b>	
Power	96 kW
Production	1300/1760 lb
Dimensions	179" x 69" x 114"
Weight	10470 lb



**STOKKERMILL™**  
RECYCLING MACHINERY

<b>M 150</b>	
Power	140 - 150 kW
Production	2200/2600 lb
Dimensions	193" x 73" x 116"
Weight	11240 lb